## MS102

Highly sensitive condenser microphone, with dual fastening stand for desk and monitor • Sensitivity: 105 dB • Frequency response: 50 – 16,000 Hz.

| | |
|---|---|
| Fixation | Base |
| Sound | Mono |
| Frequency response (KHz) | 20-17 kHz |
| Magnetic shield | Yes |

## Technical Information

Technical Specifications:

Impedance: low

Frequency Range: 20-16 kHz

Sensitivity: -62 dB+/- 3 dB

Length of cord: 1,8 m+/- 3 %

Package Contents:

MS102

Warranty card

## Shipping Information

| | Contains |
|---|---|
| Unity | 1 |
| Intermediate box | 16 |
| Export carton | 64 |
| Pallet | 768 |

## System Requirements

Stereo sound card

| | Unity | Intermediate box | Export carton |
|---|---|---|---|
| EAN | 8436001280448 | 8436001302829 | 8436001280691 |
| Weight | 2.2 | - | 9 |
| Widht | 0.145 | 0.295 | 0.652 |
| Depth | 0.02 | 0.295 | 0.345 |
| Height | 0.315 | 0.16 | 0.335 |
| | | | |
| Warranty | 2 years | | |
| | | | |
| ID de FCC/FC | | | |